

| No. | Parts Name  | Materials     | No. | Parts Name   | Materials         |
|-----|-------------|---------------|-----|--------------|-------------------|
| 15  | YOKE        | ASTM A216 WCB | 1   | Body         | ASTM A216 WCB     |
| 16  | Gland       | A182 F6a      | 2   | SEAT         | A105+STL          |
| 17  | GLANDFLANGE | ASTM A216 WCB | 3   | WEDGE        | ASTM A216 WCB+stl |
| 18  | Eyebolt     | ASTM A193 B7  | 4   | Stem         | A182 F6a          |
| 19  | Nut         | ASTM A194 2H  | 5   | Bonnet       | A105              |
| 20  | Stem nut    | ZCuAL10Fe3    | 6   | Sealing ring | ss304+graphite    |
| 21  | HANDWHELL   | KTH330-08     | 7   | Canteen ring | ASTM A276 T410    |
| 22  |             |               | 8   | Bolt         | ASTM A193 B7      |
| 23  |             |               | 9   | Plant        | A105              |
| 24  |             |               | 10  | YOKE         | ASTM A216 WCB     |
| 25  |             |               | 11  | Nut          | ASTM A194 2H      |
| 26  |             |               | 12  | Nut          | ASTM A194 2H      |
| 27  |             |               | 13  | Ping         | ASTM A1035        |
| 28  |             |               | 14  | Packing      | SS304+GRAPHITE    |

## class1500

| size | E L | d    | D1   | D2    | Н    | W   |
|------|-----|------|------|-------|------|-----|
| 8"   | 711 | φ177 | φ178 | φ 223 | 1130 | 680 |
| 6"   | 559 | φ136 | φ132 | φ172  | 900  | 600 |

|                                     | VALVE DE   | SIGN DA | TA                      |     |  |  |  |
|-------------------------------------|------------|---------|-------------------------|-----|--|--|--|
| SPECIFICATIO                        | N REQUIRED |         | ASME B16.34             |     |  |  |  |
| TYPE of VAL                         | .VE        |         | GATE                    |     |  |  |  |
| VALVE OPER                          | ATING      |         | GEAR OPEN<br>CLASS 1500 |     |  |  |  |
| VALVE PRES                          | SURE CLASS |         |                         |     |  |  |  |
| END CONNECT                         | FION TYPE  |         | BW<br>ANSI B16.10       |     |  |  |  |
| END to END I                        | DIMENSION  |         |                         |     |  |  |  |
| FLANGE DIME                         | NSION      |         | ANSI B16.25             |     |  |  |  |
| TEST                                |            |         | API 598                 |     |  |  |  |
| PAINTING or                         | COATING    |         | -                       |     |  |  |  |
| TEST                                | HYDRAULIC  | s       | HELL : 37.5             | Mpa |  |  |  |
| PRESSURE                            | HIDRAOLIC  | s       | Mpa                     |     |  |  |  |
|                                     | PNEUMATIC  | s       | EAT 27.5                | Mpa |  |  |  |
| Date                                | REV, No.   |         | DESIGNED                |     |  |  |  |
| DWG. No.                            |            |         | REVIEWED                |     |  |  |  |
| CLIENT                              |            |         | APPROVED                |     |  |  |  |
| TITLE                               | GATE VALVE |         |                         |     |  |  |  |
| STV Valve Technology Group Co., Ltd |            |         |                         |     |  |  |  |