



SPECIFICATIONS			
Nominal pressuer		2500lb	
Testing Pressuer	Shell testing	63	MPa
	Seat testing	46.2	
	Backseat testing	/	
	Air seat testing	0.6	
Max, Temperature		-29~120	°C

NPS	DN	L	W	H	d
3/4"	20	125	146	68	18

14		HANDLE	GALANIZED STEEL			
13		WASHER	A3			
12		NUT	SS304			
11		STEM WASHER	SS304			
10		O RING	RUBER			
9		STEM PACKING	RPTFE			
8	Q11F-2500CLASS-05	STEM	SS316			
7	Q11F-2500CLASS-04	SEAT	PEEK			
6	Q11F-2500CLASS-03	BALL	SS316			
5		STEM PACKING	316+GRAPHITE			
4		NUT	A194 2H			
3		STEM	SS316			
2	Q11F-2500CLASS-02	CAP	C95800			
1	Q11F-2500CLASS-01	BODY	C95800			

NO	MODEL	PART NAME	MATERIAL			
Three piece consturction design ball Valve CLASS 2500#-C95800 body/SS316 trim full bore body floating type fire safety .Female NPT end,lever operated						
Approved	Jake			Scale		
Check	Marry			1:1		
Designer	Mark			First lpage, total lpage		