



Performance Specification

Nominal Pressure		600LB	
Pressure Test	Shell Test	15.0	MPa
	Back Seal Test	7.5	
	Seal Test	0.6	
	Air Seal Test	0.6	
Suitable Temperature		-29~550 °c	
Suitable Media		Water/Steam/Oil	

Standards:

- 1.Design And Manufacture: BS 1873.
- 2.Pressure Test: API598.
3. Face To Face: ASME B16.10.
4. Flanged End: ASME B16.5.
5. Pressure Temperature Ratings: ASME B16.34

8	Bonnet	A217 WC6	16	Nut	A194
7	Gasket	304+Graphite	15	Eye Bolt	A193
6	Nut	A194 2H	14	Lubricator	H62
5	Bolt	A193 B7	13	Lock Nut	A193
4	Disc Cover	A217 WC6	12	Handwheel	A216 WCB
3	Stem	F316	11	Stem Nut	QT400-15
2	Disc	316	10	Packing Gland	A216 WCB
1	Body	A217 WC6+STL	9	Packing	Soft Graphite
NO	Parts Name	Material	NO	Parts Name	Material

8"	600	930	650	419	349	302	269.88	7.92	11.91	55.6	6.4	12-ø32
6"	559	785	550	356	292	241	211.12	7.92	11.91	47.7	6.4	12-ø29
3"	356	400	280	210	168	146	123.83	7.92	11.91	32	6.4	8-ø22
2"	292	360	250	165	127	108	82.55	7.92	11.91	25.4	6.4	8-ø19
NPS	L	H	W	D	k	d	d1	E	F	C	f	n-ød

A217 WC6		
ANSI GLOBE VALVE		
		J41Y-600LB(RJ)